

Kelin Polyurea Tile Grout adalah produk terbalik baru. Karena ketahanan aus yang sangat baik polyurea, tahan korosi, tahan kuning, tahan suhu tinggi dan kinerja superior lainnya, ia banyak digunakan dalam industri militer, kedirgantaraan dan kapal. Selain itu, itu mengeras dengan cepat, konstruksi dan tepi bersih pada hari yang sama, menghemat waktu dan biaya tenaga kerja. Lebih penting lagi, dapat dibangun di permukaan subbase basah, yang sangat memecahkan masalah yang tidak dapat dibangun karena iklim dan alasan lainnya. Produk penelitian dan pengembangan bersama Australia untuk membuat kinerja yang lebih baik, dan melalui Akademi Ilmu Pengetahuan Tiongkok Panduan Kualitas Strategis, untuk membuat produk "berkualitas stabil.

Produk dapat lebih baik digunakan dalam sambungan ubin keramik, batu, kaca, ubin mosaik di dinding atau tepung di kamar mandi, dapur, kamar tidur dan sebagainya. Cina Kelin. **Pabrikasi Filler Epoxy Gap** telah berada di bidang ini selama 14 tahun. Kami memiliki tim R & D kami sendiri dan pabrik. Karena perlindungan lingkungan material yang mudah konstruksi, dapatkan bantuan konsumen yang luas. Jadi Kelin. **pemasok perekat ubin** akan memberi Anda produk-produk berkualitas.



**Varietas warna untuk pilihan Anda. Juga berikan warna khusus.**

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



**Berikan Solusi Kesenjangan Seluruh Kamar**



**Proses konstruksi singkat**



01  
Clean the tiles and keep it dry



02  
Polish with tile wax except the glazed tile



03  
Open & Watch, both sides can extruded meanwhile



04  
Screw on the nozzle, put on the grout gun



05  
Inclined cut the top of the nozzle in 45°



06  
Squeeze out 60-80cm long grout in the forepart



07  
Evenly squeeze out the tile agent along the gap



08  
Press the grout with professional glue-press tools



09  
Don't touch in 4-5 hours and remove excess grout then.



10  
Keep the tiles dry in 24 hours

### Alat berdekatan bersama profesional



Two Component Caulking Gun



02  
Cutter Knife



03  
Pointing trowel



04  
Brush



05  
Forming Stick



06  
Perching Knife



07  
Masking Tape



08  
Stainless Steel Ball



09  
Cleaning Awl

### Keuntungan Perusahaan



### Pabrik Ikhtisar



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

### Sertifikasi

