

nat ubin kelin adalah produk baru untuk dekorasi rumah, yang sama sekali bukan agen jahit. Pada saat yang sama, itu adalah bukti cetakan, bukti kelembaban, rasa ramah lingkungan, tidak beracun dan bersih, menambahkan ion oksigen negatif untuk memurnikan udara. Lebih penting lagi, tanpa terus menerus terkena sinar matahari dengan intensitas tinggi, produk tidak akan menguning, mudah dibersihkan dan tahan terhadap kotoran. Nat ubin sangat mudah dibangun. Ini memiliki variasi warna yang bagus, kilau cerah dan permukaannya cerah seperti porselen setelah perawatan. kelin kualitas tinggi [Cina pompa injeksi nat pemasok](#), Selamat datang untuk menghubungi kami.

Produk ini dapat lebih baik digunakan pada sambungan ubin keramik, batu, kaca, ubin mosaik di dinding atau tepung di kamar mandi, dapur, kamar tidur dan sebagainya. Produk penelitian dan pengembangan bersama Australia untuk membuat kinerja yang lebih baik, dan melalui bimbingan kontrol kualitas strategis Akademi Ilmu Pengetahuan China, untuk membuat kualitas produk stabil. [nat ubin epoksi Cina pabrikan](#) untuk menyediakan Anda dengan produk berkualitas.



**Varietas warna untuk pilihan Anda. Juga menyediakan warna kustom.**

- Gray 1#
- Gray 2#
- Gray 3#
- Gray 4#
- Gray 5#
- Gray 6#
- Gray 7#
- Gray 8#
- Gray 9#
- Cement Gray
- Dull Gray
- Silver Gray
- Metal Gray
- Luxury Silver
- Glacier White
- Calaeatta
- Pearl Gold
- Slate Gray
- Terra Brown
- Greyish Green
- Yellow Gray
- Soft Khaki
- Yellowish Brown
- Olive Brown
- Brownness
- Dark Brown
- Reddish Brown
- Rock Bslack



**Berikan Solusi Kesenjangan Seluruh Kamar**



**Proses Konstruksi Singkat**



01 Clean the tiles and keep it dry



02 Polish with tile wax except the glazed tile



03 Open & Watch, both sides can extruded meanwhile



04 Screw on the nozzle, put on the grout gun



05 Inclined cut the top of the nozzle in 45°



06 Squeeze out 60-80cm long grout in the forepart



07 Evenly squeeze out the tile agent along the gap



08 Press the grout with professional glue-press tools



09 Don't touch in 4-5 hours and remove excess grout then.



10 Keep the tiles dry in 24 hours

### Alat Press Bersama Profesional



Two Component Caulking Gun



02 Cutter Knife



03 Pointing trowel



04 Brush



05 Forming Stick



06 Perching Knife



07 Masking Tape



08 Stainless Steel Ball



09 Cleaning Awl

### Keuntungan Perusahaan



### Ikhtisar Pabrik



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

### Sertifikasi

