

Kelin Polyurea Tile Grout adalah produk terbalik baru. Karena ketahanan aus yang sangat baik polyurea, tahan korosi, tahan kuning, tahan suhu tinggi dan kinerja superior lainnya, ia banyak digunakan dalam industri militer, kedirgantaraan dan kapal. Selain itu, itu mengeras dengan cepat, konstruksi dan tepi bersih pada hari yang sama, menghemat waktu dan biaya tenaga kerja. Lebih penting lagi, dapat dibangun di permukaan subbase basah, yang sangat memecahkan masalah yang tidak dapat dibangun karena iklim dan alasan lainnya. Produk penelitian dan pengembangan bersama Australia untuk membuat kinerja yang lebih baik, dan melalui Akademi Ilmu Pengetahuan Tiongkok Panduan Kualitas Strategis, untuk membuat produk "berkualitas stabil.

Produk dapat lebih baik digunakan dalam sambungan ubin keramik, batu, kaca, ubin mosaik di dinding atau tepung di kamar mandi, dapur, kamar tidur dan sebagainya. Cina Kelin. **Produsen Agen Seaming.** telah berada di bidang ini selama 14 tahun. Kami memiliki tim R & D kami sendiri dan pabrik. Karena perlindungan lingkungan material yang mudah konstruksi, dapatkan bantuan konsumen yang luas. Jadi Kelin. **Pemasok Pengisi Gap Epoksi** akan memberi Anda produk-produk berkualitas.



Varietas warna untuk pilihan Anda. Juga berikan warna khusus.

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



Berikan Solusi Kesenjangan Seluruh Kamar



Proses konstruksi singkat



01
Clean the tiles and keep it dry



02
Polish with tile wax except the glazed tile



03
Open & Watch, both sides can extruded meanwhile



04
Screw on the nozzle, put on the grout gun



05
Inclined cut the top of the nozzle in 45°



06
Squeeze out 60-80cm long grout in the forepart



07
Evenly squeeze out the tile agent along the gap



08
Press the grout with professional glue-press tools



09
Don't touch in 4-5 hours and remove excess grout then.



10
Keep the tiles dry in 24 hours

Alat berdekatan bersama profesional



Two Component Caulking Gun



02
Cutter Knife



03
Pointing trowel



04
Brush



05
Forming Stick



06
Perching Knife



07
Masking Tape



08
Stainless Steel Ball



09
Cleaning Awl

Keuntungan Perusahaan



Pabrik Ikhtisar



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

Sertifikasi

